

***PROUDLY MADE IN USA AT AN ISO 9001 CERTIFIED FACILITY***

# **WOOD SEALER X-1**

**NON-FLAMMABLE, NON TOXIC AND WATER BASED  
ENVIRONMENTALLY FRIENDLY**

***Forms an invisible protective internal barrier to harden, preserve and waterproof all types of wooden surfaces.***

**Directions:** It is recommended that **WOOD SEALER X-1** is brushed, rolled or low pressure sprayed onto the completely cleaned wood surface to be protected at 40-80 deg F. Apply two coats 2 to 4 hours apart. Applying excessive amounts of sealer may form a white residue which should be removed with a stiff brush immediately.

**1. FIRST AID:**

**Eyes** – Flush with cool water for at least 15 minutes. Call a physician.

**Skin** - Wash thoroughly with soap and water. Call a physician.

**Ingestion** – Call a physician. Never give anything by mouth to an unconscious person.

**Inhalation** – If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Call a physician.

**2. SPILL CONTROL:** Eliminate all ignition sources and keep public away. Recover free product with absorbent materials and dispose of in accordance with local, State and Federal Regulations. Keep product out of sewers and water courses.

**DANGER:** Keep out of reach of children and animals.

Always wear gloves and protective goggles when using this product.

HMIS: H=2, F=0, R=0, PP=X

***NET CONTENTS: 5 Gallons (18.9L)***

**3. PROTECTIVE EQUIPMENT:** Wear safety glasses or goggles and recommended protective gloves. If exposure exceeds TLV, wear NIOSH/MSHA approved respirator.

**4. PRECAUTIONS:** Do not get in eyes, on skin or clothing. Do not take internally. Wash thoroughly after handling.

**5. GENERAL INSTRUCTIONS:** Before using this product read Material Safety Data Sheet (MSDS) which is available on website.

**Note: Emptied Container retains vapor or product residue.**

**DISCLAIMER:** The information contained herein is based on data available to us and is believed to be accurate. However, Stone Technologies, Corp makes no express or implied warranty of merchantability or fitness for a particular use. Handling, storage and use of this product by the buyer or user are beyond the control of Stone Technologies, Corp. Risks such as ineffectiveness or other unintended consequences resulting from but not limited to failure to follow label directions *will be assumed by the buyer or user. In no case will seller be held liable for consequential, special or indirect damages resulting from the handling, storage or use of this product.*